

## Deko Light GmbH 343019 Office One 343019 / UGR-Tabelle

Leuchte: Deko Light GmbH 343019 Office One 343019

<b>Blendungsbewertung nach UGR</b>											
$\rho$ Decke		70	70	50	50	30	70	70	50	50	30
$\rho$ Wände		50	30	50	30	30	50	30	50	30	30
$\rho$ Boden		20	20	20	20	20	20	20	20	20	20
Raumgröße X      Y		Blickrichtung quer zur Lampenachse					Blickrichtung längs zur Lampenachse				
2H	2H	14.1	14.8	14.9	15.7	16.7	14.2	14.9	15.1	15.8	16.9
	3H	15.1	15.7	16.0	16.6	17.7	15.1	15.7	16.0	16.6	17.7
	4H	15.5	16.1	16.4	17.0	18.2	15.5	16.1	16.4	17.0	18.1
	6H	15.9	16.5	16.9	17.4	18.6	15.9	16.4	16.8	17.3	18.5
	8H	16.1	16.6	17.0	17.5	18.7	16.0	16.5	16.9	17.5	18.6
	12H	16.2	16.7	17.1	17.6	18.8	16.1	16.6	17.0	17.5	18.7
4H	2H	14.1	14.7	15.0	15.6	16.7	14.2	14.8	15.1	15.7	16.9
	3H	15.2	15.7	16.2	16.7	17.8	15.2	15.7	16.2	16.7	17.9
	4H	15.8	16.3	16.8	17.2	18.4	15.8	16.2	16.8	17.2	18.4
	6H	16.4	16.8	17.4	17.8	19.0	16.4	16.7	17.3	17.7	19.0
	8H	16.7	17.0	17.7	18.0	19.3	16.6	16.9	17.6	17.9	19.2
	12H	16.8	17.2	17.8	18.1	19.4	16.7	17.0	17.7	18.0	19.3
8H	4H	15.9	16.2	16.9	17.2	18.5	15.9	16.2	16.8	17.2	18.4
	6H	16.6	16.9	17.6	17.9	19.2	16.5	16.8	17.6	17.8	19.1
	8H	17.0	17.2	18.0	18.2	19.6	16.9	17.1	17.9	18.1	19.4
	12H	17.3	17.5	18.3	18.5	19.8	17.1	17.3	18.1	18.3	19.6
12H	4H	15.9	16.2	16.9	17.2	18.4	15.8	16.1	16.8	17.1	18.4
	6H	16.6	16.9	17.7	17.9	19.2	16.6	16.8	17.6	17.8	19.1
	8H	17.0	17.2	18.1	18.3	19.6	16.9	17.1	17.9	18.1	19.5
Variation der Beobachterposition für Leuchtenabstände S											
S = 1.0H		+0.3 / -0.4					+0.3 / -0.5				
S = 1.5H		+0.5 / -0.7					+0.6 / -0.9				
S = 2.0H		+0.9 / -1.0					+1.2 / -1.0				
Standardtabelle		BK05					BK05				
Korrektursummand		1.0					1.0				
Korrigierte Blendindizes bezogen auf 6503lm Gesamtlichtstrom											

Die UGR-Werte werden gemäß CIE Publ. 117 berechnet. Spacing-to-Height-Ratio = 0.25.