



Artikel Nr.: 348033

Deckenaufbauleuchte, Dubhe IV, Weiß-matt, 220-240V AC/50-60Hz, 25,00 W, Warmweiß



Technische Daten

Charakteristik

Material	Metall
Farbe	Weiß-matt
Optik	
im Lieferumfang	2x Schrauben mit Dübel

Elektrische Daten

Leistung / Leistungsaufnahme	25,00 W / 25,20 W
Eingangsspannung	220-240V AC/50-60Hz
Eingangsstrom	
Fassung / Sockel	
Anzahl Sockel	
Netzgerät	inkl. LED-Netzgerät
Ansteuerung	Phasenanschnitt oder Phasenabschnitt
Anschlussmöglichkeit	Klemme
Schutzklasse I, II, III	I

Lichttechnische Eigenschaften

Leuchtmittel	LED-Modul fest
Lichtfarbe	Warmweiß
Farbtemperatur	2800 K
Lichtstrom	1800 lm
Abstrahlwinkel	120°
LED Typ	SMD
LED Anzahl	120
Strahlungsverteilung	583 nm





Artikel Nr.: 348033

Deckenaufbauleuchte, Dubhe IV, Weiß-matt, 220-240V AC/50-60Hz, 25,00 W, Warmweiß



Lichttrichtung


Dreh- und Schwenkbereich	dreh-schwenkbar
Neigungswinkel	45 °
Abstrahlverhalten	
Reflektor / Linse	

Abmessungen und Gewicht

Länge	585 mm
Breite	95 mm
Höhe	81 mm
Durchmesser	
Deckenabhängung	
Gewicht	1440 g

Sockelmaß

Länge	517 mm
Breite	60 mm
Höhe	35 mm
Durchmesser	





Artikel Nr.: 348033

Deckenaufbauleuchte, Dubhe IV, Weiß-matt, 220-240V AC/50-60Hz, 25,00 W, Warmweiß



Grenzwerte

Die Überschreitung der Grenzwerte und Betriebsspannung führt zu einer starken Verkürzung der Lebensdauer sowie Zerstörung der LED Module.

Betriebstemperatur	-5°C - +40°C
Lagertemperatur	-10°C - +40°C
IP - Schutzart	IP 20

Allgemeine Eigenschaften

Umwelteigenschaften

Energieeffizienzklasse	A+
Energieverbrauch	26 kWh/1000h

Lebensdauer

Lebensdauer	20000 h
Lichtstrom Ende Lebensdauer	0,70
Schaltzyklen	10000

IP 20

Schutz gegen das Eindringen von Fremdkörper > 50 mm. Kein Schutz gegen das Eindringen von Wasser.



Leuchte der Schutzklasse I bei der der Schutz gegen elektrischen Schlag nicht allein auf der Basisisolierung beruht, sondern die eine zusätzliche Sicherheitsvorkehrung derart enthält, dass berührbare leitfähige Teile mit Mitteln zum Anschluss an den Schutzleiter der festen Installation ausgerüstet sind, so dass im Fehlerfall der Basisisolierung berührbare leitfähige Teile nicht aktiv werden können.



Aufgrund des komplexen Herstellungsprozesses von LED stellen die angegebenen Werte nur rein statistische Größen dar und müssen nicht zwingend den tatsächlichen Parametern jedes einzelnen LED-Moduls entsprechen, sondern können von den typischen Werten abweichen.



Die Lichtquelle dieser Leuchte darf nur vom Hersteller oder einem von ihm beauftragten Servicetechniker oder einer vergleichbar qualifizierten Person ersetzt werden



Article no.: 348033

Surface mounted ceiling lamp, Dubhe IV, matt white, 220-240V AC/50-60Hz, 25,00 W, warmwhite



Technical Data

General Characteristics

Material	metal
Colour	matt white
Optics	
included in delivery	2x screws with dowels

Electrical Characteristics

Power / power consumption	25,00 W / 25,20 W
Input voltage	220-240V AC/50-60Hz
Input current	
Base (standard designation)	
Number of bases	
Power supply unit	incl. LED-power supply unit
Electronically reversible	leading edge or trailing edge
Connection possibility	clamp
Protection class I, II, III	I

Light Technical Data

Bulb	LED-module fixed
Colour Designation	warmwhite
Colour temperature	2800 K
Luminous flux	1800 lm
Beam angle	120°
LED type	SMD
LED quantity	120
Spectral power distribution	583 nm





Article no.: 348033

Surface mounted ceiling lamp, Dubhe IV, matt white, 220-240V AC/50-60Hz, 25,00 W, warmwhite



Light Direction


Rotating and tilting range	rotatable-swivel
Angle of inclination	45 °
Radiation direction	
Reflector / lense	

Dimensions & Weight

Length	585 mm
Width	95 mm
Height	81 mm
Diameter	
Suspensions from ceiling	
Product Weight	1440 g

Base dimensions

Length	517 mm
Width	60 mm
Height	35 mm
Diameter	





Article no.: 348033

Surface mounted ceiling lamp, Dubhe IV, matt white, 220-240V AC/50-60Hz, 25,00 W, warmwhite



Absolute maximum ratings

The LED will get damaged and the lifetime will decrease when you overrun absolute maximum ratings.

Working temperature	-5°C - +40°C
Storage temperature	-10°C - +40°C
IP - Code	IP 20

General product data

Environmental Characteristics

Energy label	A+
Energy consumption	26 kWh/1000h

Lifespan

Lamp life time	20000 h
Luminous flux (end of lifetime)	0,70
Number of switching cycles	10000

IP 20

Protection against penetration of foreign objects > 50 mm. No protection against penetration of water.



Lightings of Protection Class I in which the protection against electric shock is not based solely on isolation, but an additional safety measure contains such a way that accessible conductive parts are equipped with means for connection to the protective conductor of the fixed installation, so that in case of failure of the basic insulation exposed conductive parts cannot be active.



Because of the complex manufacturing process of the LED the above shown data are just a statistical size, which is not forced to be the realistic data of every LED.



The light source of this luminaire may only be replaced by the manufacturer or by a service technician appointed by him or by a comparable qualified person