

## Deko Light GmbH 707074 Ain Spot 30W / UGR-Tabelle

Leuchte: Deko Light GmbH 707074 Ain Spot 30W

Lampen: 1 x Track system3-Phases

<b>Blendungsbewertung nach UGR</b>											
ρ Decke	70	70	50	50	30	70	70	50	50	30	
ρ Wände	50	30	50	30	30	50	30	50	30	30	
ρ Boden	20	20	20	20	20	20	20	20	20	20	
Raumgröße X      Y		Blickrichtung quer zur Lampenachse					Blickrichtung längs zur Lampenachse				
2H	2H	14.7	15.3	15.0	15.5	15.7	15.8	16.4	16.0	16.6	16.8
	3H	14.6	15.2	14.9	15.4	15.6	15.6	16.2	15.9	16.4	16.7
	4H	14.5	15.0	14.8	15.3	15.6	15.6	16.1	15.9	16.4	16.6
	6H	14.4	14.9	14.8	15.2	15.5	15.5	16.0	15.8	16.3	16.5
	8H	14.4	14.9	14.7	15.2	15.5	15.5	15.9	15.8	16.2	16.5
4H	12H	14.4	14.8	14.7	15.1	15.4	15.4	15.9	15.8	16.2	16.5
	2H	14.5	15.0	14.8	15.3	15.6	15.6	16.1	15.9	16.4	16.6
	3H	14.4	14.8	14.7	15.1	15.4	15.4	15.9	15.8	16.2	16.5
	4H	14.3	14.7	14.7	15.0	15.3	15.3	15.7	15.7	16.1	16.4
	6H	14.2	14.5	14.6	14.9	15.3	15.3	15.6	15.7	15.9	16.3
8H	8H	14.2	14.5	14.6	14.8	15.2	15.2	15.5	15.6	15.9	16.3
	12H	14.1	14.4	14.6	14.8	15.2	15.2	15.4	15.6	15.8	16.2
	4H	14.2	14.5	14.6	14.8	15.2	15.2	15.5	15.6	15.9	16.3
	6H	14.1	14.3	14.5	14.7	15.2	15.1	15.3	15.6	15.8	16.2
	8H	14.0	14.2	14.5	14.6	15.1	15.1	15.3	15.6	15.7	16.2
12H	12H	14.0	14.1	14.5	14.6	15.1	15.0	15.2	15.5	15.6	16.1
	4H	14.1	14.4	14.6	14.8	15.2	15.2	15.4	15.6	15.8	16.2
	6H	14.0	14.2	14.5	14.6	15.1	15.1	15.3	15.6	15.7	16.2
12H	8H	14.0	14.1	14.5	14.6	15.1	15.0	15.2	15.5	15.6	16.1
	8H	14.0	14.1	14.5	14.6	15.1	15.0	15.2	15.5	15.6	16.1
Variation der Beobachterposition für Leuchtenabstände S											
S = 1.0H		+6.7 / -27.4					+6.6 / -29.2				
S = 1.5H		+9.5 / -29.4					+9.4 / -31.7				
S = 2.0H		+11.5 / -31.2					+11.4 / -33.3				
Standardtabelle		BK00					BK00				
Korrektursummand		-3.9					-2.9				
Korrigierte Blendindizes bezogen auf 2391lm Gesamtlichtstrom											

Die UGR-Werte werden gemäß CIE Publ. 117 berechnet. Spacing-to-Height-Ratio = 0.25.