



Our FACADO-series bollard lights feature IP65 degree of protection for excellent weather resistance. Choose between an opal diffuser or a transparent diffuser with smoked glass to suit your requirements. The series is available in two different sizes (650 mm/1,000 mm) and features an E27 socket for replaceable lamps. The newly designed lamp head provides significantly improved illumination. The FACADO light is made of high-quality, high-pressure die-cast aluminium and is available in dark grey or rust and in square or round designs.

The IP67 connection box features a double M20 cable gland suitable for buried cables in sizes 3x1.5 mm², 5x1.5 mm² or 3x2.5 mm², and more.

Special features

- IP65 weather resistance
- IP67 connection box suitable for buried cables 3x1.5 mm²/5x1.5 mm²/3x2.5 mm², and more
- newly designed lamp head for improved illumination
- available with an opal diffuser or a transparent diffuser with smoked glass
- ideal for e.g. ST64 bulbs and A60/70 bulbs

| | |
|--------------------------------------|---|
| Housing Material | Aluminium, Polycarbonate |
| Housing Color | Rust |
| Housing Surface | Matt |
| Material of Lens | Polycarbonate - PC |
| Colour of Lens | Smoke-coloured |
| Surface Structure of Lens | Transparent |
| Protection Class | Protection class I/protective grounding |
| max. Power | 1x max. 20 W |
| Rated Input Voltage Frequency | 220-240 V/AC 50 / 60 Hz |
| Socket Description | E27 |
| Illuminant Design | A60, A70, ST64 |
| Socket Quantity | 1 |
| Connection Type | Connectionbox |
| Dimmable | Yes |
| Control | Dimmable via optional light source |
| Motion Detector | No |
| Execution | Without lamp |
| Light Exit Surfaces | 5 |
| Light characteristics | Direct |
| Light direction | Top, Side |
| Height | 650 mm |
| Diameter | 108 mm |
| Product weight | 1909 g |
| Working Temperature | -20 to 40 °C |
| Storage Temperature | -10 to 60 °C |
| IP Protection Class | IP 65 |