


Artikel Nr.: 847015

LED Bar / Tube, Litus, IP67

Technische Daten
Abmessungen und Gewicht

Länge	1000,00
Breite	26,00
Höhe	26,00
Gewicht	1390 g
Schnittmöglichkeit (je)	


Elektrische Daten

Leistung / Leistungsaufnahme	/ 10,00 W
Eingangsspannung	24V DC
Eingangsstrom	
Anschlussmöglichkeit	offene Kabel
Schutzklasse I, II, III	III

Lichttechnische Eigenschaften

Lichtfarbe	Warmweiß
Farbtemperatur	3000 K
Lichtstrom	130 lm
Abstrahlwinkel	115°
LED Typ	SMD 3528
LED Anzahl	96

Grenzwerte

Die Überschreitung der Grenzwerte und Betriebsspannung führt zu einer starken Verkürzung der Lebensdauer sowie Zerstörung der LED Module.

Betriebstemperatur	-20°C - +40°C
Lagertemperatur	-30°C - +40°C
IP - Schutzart	IP67



Artikel Nr.: 847015

LED Bar / Tube, Litus, IP67


Allgemeine Eigenschaften

Umwelteigenschaften

Energieeffizienzklasse	
Energieverbrauch	10 kWh/1000h

Lebensdauer

Lebensdauer	20000 h
Lichtstrom Ende Lebensdauer	0,70
Schaltzyklen	10000




IP67	Geschützt gegen das Eindringen von Staub. (Staubdicht) Geschützt gegen zeitweiliges Untertauchen.
	Leuchte der Schutzklasse III Leuchte, bei der der Schutz gegen elektrischen Schlag auf der Anwendung der Schutzkleinspannung (SELV) beruht und in der Spannungen höher als SELV nicht erzeugt werden.
	Aufgrund des komplexen Herstellungsprozesses von LED stellen die angegebenen Werte nur rein statistische Größen dar und müssen nicht zwingend den tatsächlichen Parametern jedes einzelnen LED-Moduls entsprechen, sondern können von den typischen Werten abweichen.
	Die Lichtquelle dieser Leuchte darf nur vom Hersteller oder einem von ihm beauftragten Servicetechniker oder einer vergleichbar qualifizierten Person ersetzt werden

Article no.: 847015

LED Bar / Tube, Litus, IP67

Technical Data**Dimensions & Weight**

Length	1000,00
Width	26,00
Height	26,00
Product weight	1390 g
Cutting possibility (each)	

**Electrical Characteristics**

Power / power consumption	/ 10,00 W
Input voltage	24V DC
Input current	
Connection possibility	wire with open ends
Protection class I, II, III	III

Light Technical Data

Colour Designation	warmwhite
Colour temperature	3000 K
Luminous Flux	130 lm
Beam angle	115°
LED type	SMD 3528
LED quantity	96

Absolute maximum ratings

The LED will get damaged and the lifetime will decrease when you overrun absolute maximum ratings.

Working temperature	-20°C - +40°C
Storage temperature	-30°C - +40°C
IP - Code	IP67



Article no.: 847015

LED Bar / Tube, Litus, IP67


General product data

Environmental Characteristics

Energy Label	
Energy consumption	10 kWh/1000h

Lifespan

Lamp life time	20000 h
Luminous flux end of lifetime	0,70
Number of switching cycles	10000



IP67 Protection against penetration of dust. (complete dust protection) Protection against temporary immersion.



Lightings of Protection Class III
Luminaire in which protection against electric shock relies on supply at safety extra-low voltage (SELV) and in which voltages higher than those of SELV are not generated.



Because of the complex manufacturing process of the LED the above shown data are just a statistical size, which is not forced to be the realistic data of every LED.



The light source of this luminaire may only be replaced by the manufacturer or by a service technician appointed by him or by a comparable qualified person