

Client:

Project:

Type:

Order Code:

Quantity:



Dyna Drum SO SCS is a high output, outdoor rated, multi-color LED floodlight. It features an internal 100-277VAC power supply, onboard DMX+RDM driver, and each unit carries Acclaim's Aria wireless DMX technology inside. It comes with a narrow 8° beam standard, with optional quick-change spread lenses for wider applications. It is ideal for facade lighting applications and as an area floodlight.

SPECIFICATIONS


| | |
|-------------------------------|---|
| Colors | RGBW (W=4000K), RGBA, RGBAW (W=4000K), DW (2400K-5500K) |
| Beam Angles | 8° standard, 20°, 40°, 60°, 10° x 60° spread lens options |
| Photometrics | See page 4, up to 4,200 lumens, 187,500 center candela |
| Effective Projected Area | 1.16 ft ² |
| Control | DMX+RDM, manual color setting in menu, photocell included, Aria wireless direct connect |
| Max Fixtures in Series | 32 via DMX, power local to each fixture |
| Power Consumption | 150W maximum |
| Operating Voltage | 100-277VAC, 50/60 Hz |
| Lumen Maintenance | L70 @ 150,000 hours (25° C) |
| Mounting | Surface mount bracket included, optional tenon mount and pipe clamp available |
| Finish | Gray standard (RAL 7047), black, white, and custom colors optional |
| Material | Die cast aluminum, polycarbonate lens, optional marine coating available |
| Ambient Operating Temperature | -40° F to 125° F (-40° C to 51° C) |
| IP Rating | IP66, wet location |
| IK Rating | IK07, protection against 2 joule impact |
| Fixture Connectors | Attached 5' (1.5m) IP66 hybrid cable, AC power +DMX/RDM |
| Warranty | 5 Years, limited |
| Weight | 30.6 lbs. (13.8 kg) |
| Dimensions | L: 14.17" x W: 13.3" x D: 8.38" (360mm x 338mm x 213mm) |

Certifications



ORDER CODES

* indicates special order



RELATED COMPONENTS

Optional Beam Accessories




DDSSL20
20° Spread lens for Dyna Drum SO


DDSSL40
40° Spread lens for Dyna Drum SO

DDSSL60
60° Spread lens for Dyna Drum SO

DDSSL1060
10° x 60° Spread lens for Dyna Drum SO




DDSOFG Full snoot for Dyna Drum SO, Gray
DDSOFSB Full snoot for Dyna Drum SO, Black
DDSOFSW Full snoot for Dyna Drum SO, White



DDSOHSG Half snoot for Dyna Drum SO, Gray
DDSOHSB Half snoot for Dyna Drum SO, Black
DDSOHSW Half snoot for Dyna Drum SO, White

RELATED COMPONENTS

Optional Mounting Accessories



TM2

Use with 2" pipe, schedule 40 tenon mount
(2.51", 56mm inner dia.)

TM4

Use with 3.5" pipe, schedule 40 tenon mount
(4.13", 105mm inner dia.)





PC2

Use with 2" pipe, schedule 40 pipe clamp
mounts 1 or 2 fixtures


PC4

Use with 4" pipe, schedule 40 pipe clamp
mounts 1 or 2 fixtures

DIMENSIONS



WIRING



PHOTOMETRICS

| Color / Beam | Lumens | Center Candela | Efficacy (l/pw) | CRI (Ra) White LED | TM30 |
|--------------|--------|----------------|-----------------|-----------------------|------|
| RGBW | TBA | | | | |
| RGBA | TBA | | | | |
| RGBAW | 3,986 | 187,507 | 27 | 72.7 | 70.1 |
| DW | TBA | | | | |